

Product Description:

Spryte™ LED downlight range is the ideal energy efficient non-fire rated solution for new build or retrofit halogen, R63 and R80 reflector lamp installations. Fitted with the edge-to-edge, multifaceted 60° wide beam EnFiniti™ lens, these downlights allow for high light output and low glare while still providing a sparkling halogen like optical appearance in a compact sized fitting. Now also available in 8W ball-joint adjustable version alongside the fixed for maximum application flexibility.

Product Image:



Product Features:

- Energy efficient LED downlight for new build or halogen and reflector lamp retrofit applications
- ThermoTec™ technology utilises a combination of highly efficient LED light source, aluminium heat sinking and thermoplastic material for longer life and consistent performance
- EnFiniti™ edge-to-edge multifaceted polycarbonate lens creates low glare and halogen like appearance
- Compact integrated driver for easy installation and low ceiling voids
- 8W supplied with fixed white bezel. 10W supplied with interchangeable round & square white bezels
- Ideal for residential applications such as corridors, bedrooms, dining rooms, lounge areas and zone 2 of bathrooms
- Pre-wired with 500mm 2 core cable
- Fixed & adjustable versions IP44 rated
- 1.5kV surge protection
- 3 year warranty

8W Fixed Integrated IP44 Dimmable LED Downlight

Product Specs:

| | | | |
|-----------------------|---------|-----------------------|-------------|
| Technology | LED | Number of LEDs | 24 |
| Lifetime L70 (hrs) | 25000 | Input Voltage | 220~240V AC |
| Input Frequency | 50/60HZ | Surge Protection (kV) | 1.5 |
| Power Factor | 0.5 | Dimmable | Yes |
| IP Rating | IP44 | Cutout Diameter (mm) | 60 |
| Overall Diameter (mm) | 78 | Overall Height (mm) | 53 |
| Recess Depth (mm) | 60 | | |

SKU Table and Ordering

| Cat No. (SKU Code) | Wattage | Lumens | Lumens/Watt | Colour | Ra | Beam Angle | SDCM |
|--------------------|---------|--------|-------------|--------|----|------------|------|
| EN-DDL10160/40 | 8W | 570lm | 71.25 | 4000K | 80 | 60° | 6 |
| EN-DDL10160/30 | 8W | 550lm | 68.75 | 3000K | 80 | 60° | 6 |

Warranty

Please contact Aurora for specifics concerning warranty on this product. The warranty is invalid in the case of improper use, installation, tampering, and removal of the Q.C. date label; installation in an improper working environment or installation not according to the current edition of the National Electric Code. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Enlite Sales

16 Alban Park Hatfield Road St. Albans
AL4 0JJ

United Kingdom

Tel : +44 (0) 1727 83 66 11

Fax : +44 (0) 1727 83 66 22

UK Enlite Distribution

Apex Park 6 Little Burrow Welwyn
Garden City AL7 4SW

United Kingdom

Tel : +44 (0) 1707 35 18 20

Fax : +44 (0) 1727 35 18 21