VETRO ROUND FIRE-RATED 5734

astro

SKU 1254010



PRODUCT SPECIFICATION

GENERAL

FINISH:BlackCABLE LENGTH:Not ApplicableMAIN MATERIAL:Glass - FloatGROSS WEIGHT:0.694 (Kg)DIMENSIONS:H: Not Applicable W: Not ApplicableCLASS:CE (Class III)

MENSIONS: H: Not Applicable W: Not Applicable CLASS: CE (Class III)

D: 94mm IP RATING: IP65

INSTALLATION ORIENTATION: Ceiling Mount BATHROOM ZONE: Zone 1, 2, 3

CUT OUT HOLE: 76mm/3in VOLTAGE: Constant Current 350 (mA)

L70:

RECESS DEPTH: 124mm PRODUCT F MARK: Not Applicable FIRE RATING: 90 min

LAMP

LIGHT SOURCE: COB LED MACADAM ELIPSE: 2-Step MAXIMUM WATTAGE: 6W UGR: To Be Advised MAXIMUM LAMP LENGTH: Not Applicable **BEAM ANGLE:** 20.4 (Degrees) LAMP INCLUDED? Yes (Integral) TILT ADJUSTMENT ANGLE: Not Applicalbe **LUMINOUS FLUX:** 614.3 (lm) ROTATION ADJUSTMENT ANGLE: Not Applicable **COLOUR TEMP:** AVERAGE LIFESPAN: 2700 (K) 36,300 (Hrs)

CRI: 80 **R9**: 14

ELECTRICAL

SWITCHED:NoSUPPLY FREQUENCY:Not ApplicableDIMMABLE:YesDRIVER/BALLAST VOLTAGE:Not ApplicableDIMMING METHOD:Control Gear DependantDRIVER AVERAGE LIFESPAN:Not Applicable

DRIVER OUTPUT CURRENT: Not Applicable EFFICACY: 49.74 (Im/W)

DRIVER OUTPUT VOLTAGE: Not Applicable DRIVER/BALLAST INCLUDED? No

ADDITIONAL INFORMATION





BOX QUANTITY X12


Œ


To Be Advised











Astro Lighting Ltd. G2 River Way, Harlow, CM20 2DP, Great Britain

T: +44 (0) 1279 427001

F: +44 (0) 1279 427002

sales@astrolighting.co.uk

www.astrolighting.co.uk