

# ARTA LED 7901

SKU 1309009

astro



## PRODUCT SPECIFICATION

### GENERAL

|                                  |                                  |                        |  |
|----------------------------------|----------------------------------|------------------------|--|
| <b>FINISH:</b>                   | Painted Black                    | <b>CABLE LENGTH:</b>   | Not Applicable                               |
| <b>MAIN MATERIAL:</b>            | Metal - Mild Steel               | <b>GROSS WEIGHT:</b>   | 1.44 (kg)                                    |
| <b>DIMENSIONS:</b>               | D: 76mm DIA: 275mm               | <b>CLASS:</b>          | CE (Class I)                                 |
| <b>INSTALLATION ORIENTATION:</b> | Wall Mount - Horizontal/Vertical | <b>IP RATING:</b>      | IP54   |
| <b>CUT OUT HOLE:</b>             | Not Applicable                   | <b>BATHROOM ZONE:</b>  | Zone 1, 2, 3                                 |
| <b>RECESS DEPTH:</b>             | Not Applicable                   | <b>VOLTAGE:</b>        | Mains 230V                                   |
| <b>FIRE RATING:</b>              | Not Applicable                   | <b>PRODUCT F MARK:</b> | Suitable for mounting on flammable materials |

### LAMP

|                             |                |                                   |                |
|-----------------------------|----------------|-----------------------------------|----------------|
| <b>LIGHT SOURCE:</b>        | LED Board      | <b>MACADAM ELIPSE:</b>            | 3000K          |
| <b>MAXIMUM WATTAGE:</b>     | 1 x 11.65W     | <b>UGR:</b>                       | To Be Advised  |
| <b>MAXIMUM LAMP LENGTH:</b> | Not Applicable | <b>BEAM ANGLE:</b>                | To Be Advised  |
| <b>LAMP INCLUDED?</b>       | Yes (Integral) | <b>TILT ADJUSTMENT ANGLE:</b>     | Not Applicable |
| <b>LUMINOUS FLUX:</b>       | 772 (lm)       | <b>ROTATION ADJUSTMENT ANGLE:</b> | Not Applicable |
| <b>COLOUR TEMP:</b>         | 3003 (K)       | <b>AVERAGE LIFESPAN:</b>          | 25,000 (Hrs)   |
| <b>CRI:</b>                 | 85             | <b>L70:</b>                       | To Be Advised  |
| <b>R9:</b>                  | 17.4           |                                   |                |


### ELECTRICAL

|                               |                |                                 |                |
|-------------------------------|----------------|---------------------------------|----------------|
| <b>SWITCHED:</b>              | No             | <b>SUPPLY FREQUENCY:</b>        | 50/60 (Hz)     |
| <b>DIMMABLE:</b>              | No             | <b>DRIVER/BALLAST VOLTAGE:</b>  | 230-240 (V)    |
| <b>DIMMING METHOD:</b>        | Not Applicable | <b>DRIVER AVERAGE LIFESPAN:</b> | To Be Advised  |
| <b>DRIVER OUTPUT CURRENT:</b> | 350 (mA)       | <b>EFFICACY:</b>                | 66.26 (lm/W)   |
| <b>DRIVER OUTPUT VOLTAGE:</b> | Not Applicable | <b>DRIVER/BALLAST INCLUDED?</b> | Yes (Integral) |

## ADDITIONAL INFORMATION



1000 HOURS SALT-SPRAY TESTED



BOX QUANTITY X6

PRODUCT ELEVATIONS

