

**Code:** 8HBC2XLEDITB250

## Sheer CFX | SHEER CFX RANGE | LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmers

### Product Image



NO IMAGE

<b>Insert Type</b>	2 gang 250W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer
<b>Insert Colour</b>	Connaught Bronze
<b>EAN13 Barcode</b>	5017504103422
<b>Commodity Code</b>	85365015
<b>Luckins TSI</b>	435332068
<b>ETIM Class</b>	EC000025
<b>Dimensions(Nominal)</b>	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket
<b>Fixing Hole Centres</b>	Box Fixing = 60.3mm Grid Fixing = CFX Clips
<b>Minimum Wall Box Depth</b>	35mm
<b>Switched Poles</b>	Single
<b>Current Rating</b>	0.9A Per Gang
<b>Voltage</b>	230V AC
<b>Maximum Load</b>	5-210W Per Gang
<b>Mains Frequency</b>	50Hz
<b>IP Rating</b>	IP2XD
<b>Terminal Capacity 1</b>	2X1mm <sup>2</sup>
<b>Terminal Capacity 2</b>	2X1.5mm <sup>2</sup>
<b>Earth Terminal Capacity 1</b>	5x1mm <sup>2</sup>
<b>Earth Terminal Capacity 2</b>	4X1.5mm <sup>2</sup>
<b>Earth Terminal Capacity 3</b>	3X2.5mm <sup>2</sup>
<b>Earth Terminal Capacity 4</b>	1X4mm <sup>2</sup> Multi-Strand
<b>Earth Terminal Capacity 5</b>	1X6mm <sup>2</sup>
<b>Product Class 1</b>	Face plate must be earthed
<b>Ambient Operating Temperature</b>	-5°C to +40°C
<b>Recommended Location</b>	Internal Use Only
<b>Maximum Installation Altitude</b>	2000m
<b>Standard/Approval</b>	BS EN 60669-2-1
<b>Additional Notes</b>	Trailing Edge & Leading Edge Dimmer
<b>Patents And Trade Marks</b>	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755

### Wiring



NO IMAGE

### Dimensions

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,  
4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

**T:** +44 (0)1747 860088

**E:** info@hamilton-litestat.com | **W:** www.hamilton-litestat.com

(WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 21/11/2023 E&OE