




# Z LED PLUS




405

- Industry leading super high efficiency (200 lm/W minimum) robust LED low/high bay suitable for industrial, commercial and retail applications
- Overall power consumptions reduced to offer traditional light output comparable to 100W, 150W and 200W but offering more accelerated energy savings
- High specification IP65 and IK08 ratings
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- Alternative installation options by means of drop rods, jack chain and catenary wire.
- Bracket accessories available for ceiling or wall mounting
- Pre-wired with 3M of H05RN-F cable for ease and speed of installation
- 1-10V dimmable as standard




**OCTO**  
Option  
Available

Powered by  
**CASAMBI**



AZLEDPLUS/REF -  
Aluminium Reflector



AZLEDPLUS/FB1 -  
Mounting Bracket

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP	IK
220/240V	50/60Hz	-35°C to 50°C	L80 100,000	70	4	110°	1	IP65	IK08

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	A	B
AZLEDPLUS/1		75W		15000lm		265mm	152mm
AZLEDPLUS/2	Cool White	115W	4000K	23000lm	200lm	265mm	152mm
AZLEDPLUS/3		150W		30000lm		300mm	162mm

\* For Daylight variant add 'DL' at the end of the above codes e.g. **AZLEDPLUS/1/DL**

CODE (OPTIONS)	DESCRIPTION
/DL	Daylight Versions
/M3	Emergency
/OCTO	OCTO Smart Control
/DD	Digital Dimming (DD3)
/MWS	Microwave Sensor

CODE (ACCESSORIES)	DESCRIPTION
AZLEDPLUS/REF1	Z LED PLUS 1 & 2 High Bay Aluminium Reflector
AZLEDPLUS/REF2	Z LED PLUS 3 High Bay Aluminium Reflector
AZLEDPLUS/FB1	Z LED PLUS High Bay Mounting Bracket

