


Kamar



- High performance projector with a vast number of customisation options suitable for all commercial, hospitality, retail and industrial applications
- Die-cast construction provides sleek and modern appearance, perfect for architectural applications
- Beam angle options ranging from 8° up to 60° ensure suitability for most applications
- Multiple control options available, DALI (as standard), DMX and Casambi (35W and 100W only) as well as an extensive collection of CCT options (2000K, 2200K, 2700K, 3000K, 4000K, 5000K, TW, RGBW) provide complete control and light output for even the most complex of projects
- Low glare hood and honeycomb film accessories available for projects when glare optimisation and upward lighting are considerations




OCTO
Option
Available

Powered by
CASAMBI



DIMENSIONS	A	B	C
AKAR1	330mm	219.5mm	100mm
AKAR3	452mm	450mm	160mm
AKAR4	452mm	450mm	160mm



Fitted with Hood and
Spike Accessory



RGB

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	CLASS	IP	IK
220/240V	50/60Hz	-30°C to 50°C	L70 54,000	80	1	IP66	IK08

MODEL	REVISION	CCT	BEAM ANGLE	CONTROLS
AKAR1 35W	1	22 2200K	NB 8° Symmetrical	DD3 DALI
AKAR3 100W		27 2700K	MB 12° Symmetrical	DMX RDM DMX
AKAR4 150W		30 3000K	WB 30° Symmetrical	OCTO OCTO (35W and 100W only)
		40 4000K	UWB 60° Symmetrical	
		50 5000K	ASY 20° x 60° Asymmetrical	
		TW Tunable White		
		RGBW27 RGBW & 2700K		
		RGBW30 RGBW & 3000K		
		RGBW40 RGBW & 4000K		

SELECT A WATTAGE

Example - **AKAR1** = 35W

SELECT A CCT OPTION

Example - **22** = 2200K

SELECT A BEAM ANGLE OPTION

Example - **NB** = 8° Symmetrical

SELECT A BEAM ANGLE OPTION

Example - **DD3** = DALI

CODE (ACCESSORIES)	DESCRIPTION
AKAR1/1/SA	Ground Spike Accessory
AKAR1/1/CP/RGBW	RGBW Connector Plug

CODE (ACCESSORIES)	DESCRIPTION
AKAR1/1/HA	Hood Accessory (35W)
AKAR2/1/HA	Hood Accessory (100W & 150W)
AZLZED/40-150PCA	40-150mm Pole Clamp Accessory (100W & 150W)

