

www.hamilton-litestat.com

Item Image Wiring 2 Way and Intermediate Switching Wiring Methods **Dimensions** Hamilton SHEER CFX 6 GANG 2 WAY 1 DAX ROCKER SWITCH

89C R26 AB-B

Sheer CFX Antique Brass 6 gang 2 Way 10AX Rocker. Standard Insert will be Antique Brass with a Black surround.

Primary Range	Sheer CFX	
Insert Type	2 Way Rocker Switches	
Plate Finish	Antique Brass	
Frame Finish		
Switch Colour	Antique Brass	
Body & Switch Trim	Black	
Height	Double = 86mm	
Width	Double = 145mm	
Depth	Double = 4.5mm	
Fixing Hole Centres	Box Fixing = 120.6mmBox Fixing = 120.6mm	
Minimum Wall Box Depth	25mm	
Wattage		
Switched Poles	Single	
Current Rating	10AX	
Voltage	220/250V AC	
Max load	10 Amp inductive	
Contact Gap Minimum	3mm	
Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 3	1 x 2.5mm2	
Terminal Capacity 4	1 x 4mm2 Multi-Strand	
Terminal Capacity 5	1 x 6mm2	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-Strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed	
Ambient Operating	-5° to +40°C	
Temperature	-5 to +40 C	
Recommended Location	Indoor use only	
Standard/Approval	BS EN 60669-1	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755	

All products listed conform to current British or European standards and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.	It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as at August 2012 E&OE

R Hamilton & Co Ltd • Quarry Industrial Estate • Mere • Wiltshire • BA12 6LA • UK T: +44 (0)1747 860088 • F: +44 (0)1747 861032 • E: info@hamilton-litestat.com www.hamilton-litestat.com

Directors: R Hamilton • I Hamilton • RL Haines • CP Savory • AMH Hamilton (Secretary) Registered Office: Cedar House • Breckland • Linford Wood • Milton Keynes • MK14 6EX • Buckinghamshire Registered in London No. 941624 • VAT Registration No. 222 6607 84







